

Date Revised: 04/30/2018

Supersedes: 04/26/2018

#### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

Product Name(s): Five Star Centri-Cast® One-Pass™ WP

Five Star Centri-Cast® Pipe Repair Mortar

Five Star Centri-Cast® Pipe Repair Mortar with

Microban® Technology

Five Star Structural Concrete® Gunite WP/FS

Synonyms: Mud, Spray mortar, PRM

Product Use: Spray mortar for concrete construction and repair.

Restrictions on Use: Use per Five Star's product recommendation

Manufacturer/Supplier Five Star Products, Inc.

60 Parrott Drive

Shelton, CT 06484 USA

Phone #: 203-336-7900

Emergency Phone #: CHEM-TEL 1-800-255-3924

(Outside the U.S. 1-813-248-0585)

#### SECTION 2: HAZARD(S) IDENTIFICATION-GHS INFORMATION

Classification: Acute Oral Toxicity – Category 4

Acute Toxicity – Dermal, Category 5 Skin Corrosion/Irritation – Category 1 Sensitization – Dermal, Category 1 Eye Damage/Irritation – Category 1 Sensitization – Respiratory, Category 1

Specific Target Organ Toxicity (Single Exposure) - Cat 3

Carcinogenicity - Category 1A

Specific Target Organ Toxicity (Repeated Exposure) - Cat 2

Label Elements/Hazard Pictograms:







Signal Word: Danger

**Hazard Statements:** H302 Harmful if swallowed

H313 May be harmful in contact with skin

H314 Causes severe skin burns and eye damage

H317 May cause an allergic skin reaction

H318 Causes serious eye damage



Date Revised: 04/30/2018

Supersedes: 04/26/2018

H334 May cause allergy or asthma symptoms or breathing difficulties if

inhaled

H335 May cause respiratory irritation

H350 May cause cancer

H373 May cause damage to organs through prolonged or repeat

exposure

Precautionary
Statements/Prevention:

P260 Do not breathe dust, fume, gas, mist, vapors, or spray

P264 Wash thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P272 Contaminated work clothing should not be allowed out of the

workplace

P280 Wear protective gloves, protective clothing, eye protection and

face protection

P284 Wear respiratory protection

Response: P330, P331 If swallowed: Rinse mouth. Do NOT induce vomiting

P361, P353 If on skin (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P340 If inhaled: Remove person to fresh air and keep comfortable for

breathing.

P351 If in eyes: Rinse cautiously with water for several minutes.

P338 Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center or doctor.

P333, P313 If skin irritation or rash occurs: Get medical advice/attention. P342, P310, P363 If experiencing respiratory symptoms: Call a poison

center or doctor. Wash contaminated clothing before reuse.

**Storage:** Store locked up.

Disposal: Dispose of contents/container in accordance with applicable regional,

national, and local laws and regulations.

Hazards Not Otherwise

Classified:

Not applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS					
Hazardous Common CAS No. % wt/wt Ingredient(s) Name/Synonyms					
Portland Cement*	Hydraulic cement	65997-15-1	20-40		
Amorphous Silica Mixture	None	Trade Secret	10-20		
Quartz	Silicon Dioxide, Silica Sand	14808-60-7	40-55		

<sup>\*</sup>Portland Cement typically contains about 0.5 ppm of Cr(VI) which may affect sensitized individuals to dermatitis.



Date Revised: 04/30/2018

Supersedes: 04/26/2018

#### **SECTION 4: FIRST AID MEASURES**

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for

breathing.

If experiencing respiratory symptoms call poison center or doctor.

**Eye Contact:** If in eyes: Rinse cautiously with water for at least 30 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Immediately

call a poison center or doctor.

**Skin Contact:** If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower for at least 15 minutes. Immediately call a poison center or doctor if irritation develops. Wash contaminated clothing

before reuse.

Ingestion: If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a

poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth

to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or SDS where possible).

**Note to Physicians:** Symptoms may not appear immediately. Treat symptomatically.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

Flammability and Explosion

**Information:** Not flammable or combustible by OSHA/WHMIS criteria.

Sensitivity to Mechanical

Impact: This material is not sensitive to mechanical impact.

**Sensitivity to Static** 

Discharge:

This material is sensitive to static discharge at temperatures at or above

the flash point.

MEANS OF EXTINCTION

**Suitable Extinguishing Media:** Small Fire: Dry chemical, CO2, or water spray.

Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire-

control water for later disposal; do not scatter the material.

Unsuitable Extinguishing

Media:

Not Available

Product of Combustion:

Non-combustible

**Protection of Firefighters:** 

As in any fire, wear self-contained breathing apparatus pressuredemand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Emergency Procedures:** Use personal protective equipment. Ensure adequate ventilation. Keep

people from spill. Avoid dust formation.



Date Revised: 04/30/2018

Supersedes: 04/26/2018

Personal Precautions: Avoid inhalation of dust. Do not get into eyes, on skin, or clothing.

**Environmental Precautions:** The environmental impact of this product has not been fully investigated.

Methods for Containment: Cover powder spill with plastic sheet or tarp to minimize spreading.

Collect this material into a disposal container by sucking or sweeping up.

**Methods for Cleanup:** Pick up and transfer to properly labeled containers.

**Other Information:** See Section 13 for disposal considerations.

#### **SECTION 7: HANDLING AND STORAGE**

Handling: Wear personal protective equipment. Ensure adequate ventilation. Avoid

dust formation. Do not breathe dust. Prevent contact with skin, eyes,

and clothing. Wash thoroughly after handling.

**Storage:** Keep containers tightly closed in a cool, dry, and well-ventilated place.

Store locked up.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

Component	CAS No.	ACGIH TLV	OSHA PEL
Portland Cement	65997-15-1	TWA: 1mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction TWA: 50 mppcf; <1% Crystalline silica
Amorphous Silica Mixture	Trade Secret	Not Established	TWA: Total 15 mg/m <sup>3</sup> Respirable 5 mg/m <sup>3</sup>
Quartz*	14808-60-7	TWA: 0.025mg/m³ respirable fraction	TWA: 0.050 mg/m³ AL: 0.025 mg/m³

#### PERSONAL PROTECTIVE EQUIPMENT (PPE)

**Eye/Face Protection:** Tightly fitting safety goggles.

Hand Protection: Impervious gloves. Impervious clothing.

Skin and Body Protection: Impervious gloves. Impervious clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA

approved respiratory protection should be worn. Positive-pressure

<sup>\*</sup>Respirable (< 6 micron) fraction for product is < 0.1%



Date Revised: 04/30/2018

Supersedes: 04/26/2018

supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations:

Handle according to established industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES			
Appearance:	Gray, finely ground solid powder		
Color:	Gray		
Odor:	Mild		
Odor Threshold:	None		
Physical State:	Solid, powder		
pH:	12 when mixed with water		
Melting Point / Freezing Point:	> 1,832°F (1,000°C)		
Initial Boiling Point:	Not Available		
Boiling Point:	> 3,632°F (2,000°C)		
Flash Point:	Not Applicable		
Evaporation Rate:	Not Applicable		
Flammability (solid, gas):	Not Applicable		
Lower Flammability Limit:	Not Applicable		
Upper Flammability Limit:	Not Applicable		
Vapor Pressure:	Not Applicable		
Vapor Density:	Not Applicable		
Relative Density:	2.7 – 3.1		
Solubility:	Slight, 0.2 - 0.5%		
Partition Coefficient: n-Octanol/Water:	Not Applicable		
Auto-ignition Temperature:	Not Applicable		
Decomposition Temperature:	Not Available		
Viscosity:	Not Applicable		
Percent Volatile, wt.%:	0		
VOC Content, wt.%:	0		
Density:	2.7 – 3.1 g/cc		
Coefficient of Water/Oil Distribution:	Not Applicable		



Date Revised: 04/30/2018

Supersedes: 04/26/2018

#### **SECTION 10: STABILITY AND REACTIVITY**

**Chemical Stability:** Stable under recommended storage conditions.

**Possibility of Hazardous** 

**Reactions:** None under normal processing.

**Conditions to Avoid:** Exposure to water – product may harden on contact with water.

Manage dust formation during usage.

**Incompatible Materials:** Strong acids.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

**Product information** 

**Inhalation:** Irritating to respiratory system. Irritating to mucous membranes.

**Eye contact:** Risk of serious damage to eyes.

Skin contact: Irritating to skin. May cause allergic skin reaction. May cause alkali

burns.

**Ingestion:** Harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Portland Cement	Not Available	Not Available	Not Available

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Amorphous Silica Mixture	> 2,000 mg/kg	> 2,000 mg/kg	> 5 mg/L

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz	500 – 22,500 mg/kg (Rat)	Not Established	Not Established*

<sup>\*</sup>LCL50: 0.3 mg/m3 / 10Y (Human)

Symptoms related to the physical, chemical and toxicological characteristics:

No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

**Sensitization:** May cause sensitization by skin contact.

Mutagenic Effects: No information available.



Date Revised: 04/30/2018

Supersedes: 04/26/2018

**Carcinogenicity:** The table below indicates whether each agency has listed any ingredient

as a carcinogen. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human

carcinogen (Group 1). May cause cancer by inhalation.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz	A2*	Group 1	Known	X

<sup>\*</sup>The respirable fraction as a whole is less than 0.1% and anticipated usage would generate far less than 0.1% as a respirable quantity above exposure guidelines as noted in Section 8.

ACGIH: (American Conference of Governmental Industrial

**Hygienists):** A2 - Suspected Human Carcinogen

IARC: (International Agency

**for Research on Cancer):** Group 1 - Carcinogenic to Humans

NTP: (National Toxicity

**Program):** Known Carcinogen

OSHA: (Occupational Safety &

**Health Administration**): X - Present

**Reproductive Toxicity:** No information available.

**STOT - single exposure:** May cause respiratory irritation.

**STOT - repeated exposure:** Causes damage to organs through prolonged or repeated exposure if

inhaled. Lungs.

Chronic Toxicity: Inhalation overexposure to free crystalline silica may cause delayed lung

injury including silicosis, a disabling and potentially fatal lung disease.

**Aspiration Hazard:** No information available.

Numerical measures of toxicity - Product

The following values are calculated based on chapter

3.1 of the GHS document: LD 50 Oral: 500 mg/kg; Acute toxicity estimate

#### **SECTION 12: ECOLOGICAL INFORMATION**

**Toxicity:** The environmental impact of this product has not been fully investigated.

**Aquatic Toxicity:** The environmental impact of this product has not been fully investigated.

Persistence and

**Degradability:** No information available.

**Bio-accumulative Potential:** Does not accumulate in organisms.

**Mobility in Soil:** No further relevant information available.

**Ecotoxical Effects** 

Remark:



Date Revised: 04/30/2018

Supersedes: 04/26/2018

No information available.

Additional Ecological

**Information:** No information available.

General Notes: This statement was deduced from products with a similar structure or

composition. Due to available data on eliminability/decomposition and bio-accumulation potential prolonged term damage of the environment cannot be excluded. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies. Toxic for aquatic

organisms.

PBT Assessment: Not Available

vPvB Assessment: Not Available

Other Adverse Effects: No further relevant information available.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods** 

**Recommendation:** This material as supplied is not a hazardous waste according to Federal

regulations (40CFR261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is

processed or otherwise altered.

**Uncleaned Packaging** 

Recommendation:

Disposal must be made according to official regulations. Do not re-use

empty containers.

#### **SECTION 14: TRANSPORT INFORMATION**

US DEPARTMENT of TRANSPORTATION (DOT)

Proper Shipping Name: Not Regulated

Class: Not Applicable

UN #: Not Applicable

Packing Group: Not Applicable

CANADA Transportation of Dangerous Goods (TDG)

Proper Shipping Name: Not Regulated

Class: Not Applicable

UN #: Not Applicable

Packing Group: Not Applicable

Air Transport (ICAO-

IATA/DGR)

Proper Shipping Name: Not Regulated



Date Revised: 04/30/2018

Supersedes: 04/26/2018

Class: Not Applicable

UN #: Not Applicable

Packing Group: Not Applicable

Sea Transport (IMDG-

Code/GGVSee): Not Regulated

**UN** #: Not Applicable

Proper Shipping Name: Not Applicable

Class: Not Applicable

Packing Group: Not Applicable

Marine Pollutant: Not Applicable

**Special Provision(s):** Not Applicable

#### **SECTION 15: REGULATORY INFORMATION**

#### CHEMICAL INVENTORIES

**US (TSCA):** The components of this product are in compliance with the chemical

notification requirements of TSCA.

CANADA (DSL): The components of this product are in compliance with the chemical

notification requirements of NSN Regulations under CEPA, 1999.

U.S. FEDERAL REGULATIONS Section 313 of Title III of the Superfund Amendments and Reauthorization

Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the

CFR, Part 372.

**UNITED STATES:** This SDS has been prepared to meet the US OSHA Hazard Communication

Standard, 29 CFR 1910.1200

SARA 311/312 Hazard

Categories

Acute health hazard – Yes

Chronic Health hazard - Yes

Fire Hazard – No

Sudden Release of Pressure - No

Reactive Hazard - No

**US STATE Right to Know** 

Regulations:

Chemical Name	NJ	MA	PA	IL	RI
Portland Cement	X	х	х		X
Quartz	Х	Х	Х		Х

**California** This product contains the following Proposition 65 chemicals.

California Prop 65: Chemical Name: Quartz CAS-No: 14808-60-7 CA Prop. 65: Carcinogen



Date Revised: 04/30/2018

Supersedes: 04/26/2018

#### **SECTION 16: OTHER INFORMATION**

HMIS Rating:	Health	Flammability	Physical Hazard	Personal Protection
	1	0	1	E, X

**Disclaimer:** This information is furnished without warranty of any kind, expressed or

implied. Five Star Products, Inc. bases the information and recommendations in this document on data believed to be current and

accurate.