

Date Revised: 09/13/2022

Supersedes: 02/24/2022

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION		
Product Name(s):	Five Star [®] NSG Grout	
Synonyms:	NSG	
Product Use:	For use in general construction grouting applications	
Restrictions on Use:	N/A	
Manufacturer/Supplier	Five Star Products, Inc. 2 Enterprise Drive, Suite 303 Shelton, CT 06484 USA	
Phone #:	203-336-7900	
Emergency Phone #:	VelocityEHS 1-800-255-3924 (Outside the U.S. 1-813-248-0585)	
SECTION 2: HAZARD(S) IDE	NTIFICATION-GHS INFORMATION	
Classification:	Acute Oral Toxicity – Category 4 Skin Corrosion/Irritation – Category 1 Acute Toxicity – Dermal, Category 5 Sensitization – Dermal, Category 1 Eye Damage/Irritation – Category 1 Sensitization – Respiratory, Category 1 Specific Target Organ Systemic Toxicity (Single Exposure) – Cat 3 Carcinogenicity – Category 1A Specific Target Organ Toxicity (Repeated Exposure) – Cat 2	



Signal Word:	Danger
Hazard Statements:	H302 Harmful if swallowed
	H313 May be harmful in contact with skin
	H314 Causes severe skin burns and eye damage
	H317 May cause an allergic skin reaction
	H318 Causes serious eye damage
	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
	H335 May cause respiratory irritation
	H350 May cause cancer
	H373 May cause damage to organs through prolonged or repeated exposure

Label Elements/Hazard

Pictograms:



Date Revised: 09/13/2022

Supersedes: 02/24/2022

Precautionary Statements/Prevention:	 P260 Do not breathe dust, fume, gas, mist, vapors, or spray P264 Wash thoroughly after handling P270 Do not eat, drink or smoke when using this product P272 Contaminated work clothing should not be allowed out of the workplace P280 Wear protective gloves, protective clothing, eye protection and face protection P284 Wear respiratory protection
Response:	 P330, 331 If swallowed: Rinse mouth. Do NOT induce vomiting P361, 353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P340 If inhaled: Remove person to fresh air and keep comfortable for breathing P351, P338, P310 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a poison center or doctor P333, P313 If skin irritation or rash occurs: Get medical advice/attention. P342, P310, P363 If experiencing respiratory symptoms: Call a poison center or doctor. Wash contaminated clothing before reuse, P363.
Storage:	Store locked up.
Disposal:	Dispose of contents/container in accordance with applicable regional, national, and local laws and regulations.
Hazards Not Otherwise Classified:	Not applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS			
Hazardous Ingredient(s)	Common Name/Synonyms	CAS No.	% wt/wt
Portland Cement*	Hydraulic cement	65997-15-1	25-45
Quartz	Silicon Dioxide, Silica Sand	14808-60-7	55-75

* Portland Cement typically contains about 0.5 ppm of Cr(VI) which may affect sensitized individuals to dermatitis.



Date Revised: 09/13/2022

SECTION 4: FIRST AID MEASURES		
Inhalation:	If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms call poison center or doctor.	
Eye Contact:	If in eyes: Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.	
Skin Contact:	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower for at least 15 minutes. Immediately call a poison center or doctor if irritation develops. Wash contaminated clothing before reuse.	
Ingestion:	If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth to an unconscious person.	
General Advice:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).	
Note to Physicians:	Symptoms may not appear immediately. Treat symptomatically.	

SECTION 5: FIRE-FIGHTING MEASURES		
Flammability and Explosion Information:	Not flammable or combustible by OSHA/WHMIS criteria.	
Sensitivity to Mechanical Impact:	This material is not sensitive to mechanical impact.	
Sensitivity to Static Discharge:	None	
MEANS OF EXTINCTION		
Suitable Extinguishing Media:	Small Fire: Dry chemical, CO2, or water spray. Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire- control water for later disposal; do not scatter the material.	
Unsuitable Extinguishing Media:	Not available	
Product of Combustion:	Non-combustible	
Protection of Firefighters:	As in any fire, wear self-contained breathing apparatus pressure- demand, MSHA/NIOSH (approved or equivalent) and full protective gear.	



Date Revised: 09/13/2022

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures:	Use personal protective equipment. Ensure adequate ventilation. Keep people from spill. Avoid dust formation.
Personal Precautions:	Avoid inhalation of dust. Do not get into eyes, on skin, or clothing.
Environmental Precautions:	The environmental impact of this product has not been fully investigated.
Methods for Containment:	Cover powder spill with plastic sheet or tarp to minimize spreading. Collect this material into a disposal container by sucking or sweeping up.
Methods for Cleanup:	Pick up and transfer to properly labeled containers.
Other Information:	See Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Handling:Wear personal protective equipment. Ensure adequate ventilation. Avoid
dust formation. Do not breathe dust. Prevent contact with skin, eyes,
and clothing. Wash thoroughly after handling.Storage:Keep containers tightly closed in a cool, dry, and well-ventilated place.

Store locked up.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	CAS No.	ACGIH TLV	OSHA PEL
Portland cement	65997-15-1	TWA: 1mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction TWA: 50 mppcf <1% Crystalline silica
Quartz**	14808-60-7	TWA: 0.025mg/m ³ respirable fraction	TWA: 0.050 mg/m ³ AL: 0.025 mg/m ³

PEL: Permissible Exposure Limit TLV: Threshold Limit Value AL: Actionable Level

** Respirable(< 6 micron) fraction for product is < 0.1%.

Engineering Controls: Not normally required.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

- **Eye/Face Protection:** Tightly fitting safety goggles
- Hand Protection: Impervious gloves. Impervious clothing.



Date Revised: 09/13/2022

Supersedes: 02/24/2022

Skin and Body Protection:	Impervious gloves. Impervious clothing.
Respiratory Protection:	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations:	Handle according to established industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
Appearance:	Gray, finely ground solid powder	
Color:	Gray	
Odor:	mILD	
Odor Threshold:	None	
Physical State:	Solid, powder	
pH:	12 when mixed with water	
Melting Point / Freezing Point:	> 1832°F (1000°C)	
Initial Boiling Point:	Not Applicable	
Boiling Point:	> 3632°F (2000°C)	
Flash Point:	Not Applicable	
Evaporation Rate:	Not Applicable	
Flammability (solid, gas):	Not Applicable	
Lower Flammability Limit:	Not Applicable	
Upper Flammability Limit:	Not Applicable	
Vapor Pressure:	Not Applicable	
Vapor Density:	Not Applicable	
Relative Density:	2.70 - 3.10	
Solubility:	Slight 0.2 – 0.5%	
Partition Coefficient: n-Octanol/Water:	Not Applicable	
Auto-ignition Temperature:	Not Applicable	
Decomposition Temperature:	Not Applicable	
Viscosity:	Not Applicable	
Percent Volatile, wt.%:	Not Applicable	
VOC Content, wt.%:	Not Applicable	



Supersedes: 02/24/2022

Density:	2.71 – 3.1 g/cc
Coefficient of Water/Oil Distribution:	Not Applicable

SECTION 10: STABILITY AND REACTIVITY		
Chemical Stability:	Stable under recommended storage conditions.	
Possibility of Hazardous Reactions:	None under normal processing.	
Conditions to Avoid:	Exposure to water – product may harden on contact with water.	
Incompatible Materials:	Strong acids.	

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product information	
Inhalation:	Irritating to respiratory system. Irritating to mucous membranes.
Eye contact:	Risk of serious damage to eyes.
Skin contact:	Irritating to skin. May cause allergic skin reaction. May cause alkali burns.

Ingestion: Harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Portland Cement	Not Available	Not Available	Not Available

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz	500 – 22,500 mg/kg (Rat)	Not Established	Not Established*

*LCL50: 0.3 mg/m3 / 10Y (Human)

Symptoms related to the physical, chemical and toxicological characteristics: No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization:	May cause sensitization by skin contact.
Mutagenic Effects:	No information available.



Supersedes: 02/24/2022

Carcinogenicity:

The table below indicates whether each agency has listed any ingredient as a carcinogen. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). May cause cancer by inhalation.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz	A2*	Group 1	Known	х

*The presence of a minimal amount of crystalline silica is typical in the mineral admixture, the respirable fraction as a whole is less than 0.1% and anticipated usage would generate far less than 0.1% as a respirable quantity above exposure guidelines as noted in Section 8.

ACGIH: (American Conference of Governmental Industrial Hygienists):	A2 - Suspected Human Carcinogen
IARC: (International Agency for Research on Cancer):	Group 1 - Carcinogenic to Humans
NTP: (National Toxicity Program):	Known Carcinogen
OSHA: (Occupational Safety & Health Administration):	X - Present
Reproductive Toxicity:	No information available.
STOT - single exposure:	May cause respiratory irritation.
STOT - repeated exposure:	Causes damage to organs through prolonged or repeated exposure if inhaled. Lungs.
Chronic Toxicity:	Inhalation overexposure to free crystalline silica may cause delayed lung injury including silicosis, a disabling and potentially fatal lung disease.
Aspiration Hazard:	No information available.
Numerical measures of toxicity	- Product
The following values are calculated based on chapter 3.1 of the GHS document:	LD 50 Oral: 500 mg/kg; Acute toxicity estimate

SECTION 12: ECOLOGICAL INFORMATION	
Toxicity:	The environmental impact of this product has not been fully investigated.
Aquatic Toxicity:	The environmental impact of this product has not been fully investigated. Portland cement contains up to about 3-5% calcium oxide.
	Calcium Oxide (1305-78-8):
	 96 hour LC50 freshwater fish – Species: Cyprinus carpio =1070 mg/l (static)



Date Revised: 09/13/2022

Supersedes: 02/24/2022

• Chronic 46 day NOEC freshwater fish – Species: Oreochromis niloticus juvenile (fledgling, hatchling, weanling) = 100 mg/l

Persistence and Degradability:	No information available.
Bio-accumulative Potential:	Does not accumulate in organisms
Mobility in Soil:	No further relevant information available
Ecotoxical Effects Remark:	No information available.
Additional Ecological Information:	No information available.
General Notes:	This statement was deduced from products with a similar structure or composition. Due to available data on eliminability/decomposition and bio-accumulation potential prolonged term damage of the environment cannot be excluded. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Addition of water to cement creates an alkaline pH of between 12-13. Cured product is inert. Common to concrete construction around waterways, particular concern should be given to best practices to avoid/minimize spillage/discharge to the nearby environment as best as possible. In the case of significant spillage in confined or restricted areas, pH may increase to a level toxic to fish and aquatic organisms.
PBT Assessment:	Not Available
vPvB Assessment:	Not Available
Other Adverse Effects:	No further relevant information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Recommendation:	This material as supplied is not a hazardous waste according to Federal regulations (40CFR261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered.
Uncleaned Packaging	
Recommendation:	Disposal must be made according to official regulations. Do not re-use empty containers.

SECTION 14: TRANSPORT INFORMATION

US DEPARTMENT of	
TRANSPORTATION (DO	T)

Proper Shipping Name: Not Regulated

Class: Not Applicable



UN #:	Not Applicable
Packing Group:	Not Applicable
CANADA Transportation of Dangerous Goods (TDG) Proper Shipping Name:	Not Regulated
Class:	Not Applicable
UN #:	Not Applicable
Packing Group:	Not Applicable
Air Transport (ICAO- IATA/DGR)	
Proper Shipping Name:	Not Regulated
Class:	Not Applicable
UN #:	Not Applicable
Packing Group:	Not Applicable
Sea Transport (IMDG- Code/GGVSee):	Not Regulated
UN #:	Not Applicable
Proper Shipping Name:	Not Applicable
Class:	Not Applicable
Packing Group:	Not Applicable
Marine Pollutant:	Not Applicable
Special Provision(s):	Not Applicable

SECTION 15: REGULATORY INFORMATION

CHEMICAL INVENTORIES	
US (TSCA):	The components of this product are in compliance with the chemical notification requirements of TSCA.
CANADA (DSL):	The components of this product are in compliance with the chemical notification requirements of NSN Regulations under CEPA, 1999.
U.S. FEDERAL REGULATIONS	Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the CFR, Part 372.
UNITED STATES:	This SDS has been prepared to meet the US OSHA Hazard Communication Standard, 29 CFR 1910.1200
SARA 311/312 Hazard Categories	Acute health hazard – Yes Chronic Health hazard – Yes



Supersedes: 02/24/2022

Fire Hazard – No Sudden Release of Pressure – No

Reactive Hazard - No

US STATE Right	to	Know	
Regulations			

Chemical Name	L	MA	ΡΑ	IL	RI
Portland Cement	x	x	x		x
Quartz	x	X	x		X

California California Prop 65: This product contains the following Proposition 65 chemicals: Chemical Name: Quartz, CAS No 14808-60-7, CA Prop. 65: Carcinogen

Chemical Name: Chromium, CAS No 18450-29-9, CA Prop 65: Birth defects or other reproductive harm

SECTION 16: OTHER INFORMATION							
HMIS Rating:	Health	Flammability	Physical Hazard	Personal Protection			
	1	0	1	Е, Х			

Disclaimer: This information is furnished without warranty of any kind, expressed or implied. Five Star Products, Inc. bases the information and recommendations in this document on data believed to be current and accurate.